


Project:

Type:

Prepared By:

Date:



UPC: 192552015400

Features and Benefits

Replace traditional 18W/32W fluorescent linear tubes
 Built-in lithium batteries for emergency lighting
 Reduces maintenance and replacement costs with longer lifespan
 Provides 90 minutes of light at 400 lumens under emergency use
 50,000-hour LED lifespan
 Rated for use in enclosed fixtures in dry or damp locations
 5-Year, No-Compromise Warranty

Technical Specifications

Performance

Description:

Designed and engineered as an all-in-one general purpose lighting and battery powered emergency backup LED solution.

Product Type:

Linear Tube

Wattage Equivalency:

32W T8 Fluorescent

Input Wattage:

17W

Lumens:

2,105lm

Efficacy:

124lm/W

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

Electrical

Dimmable:

Yes

Dimming Type:

TRIAC/ELV @ 120V

Input Voltage:

120-277V

Operating Frequency:

50/60Hz

Operating Temperature:

32°F to 104°F (0°C to 40°C)

Battery Operation:

90 minutes

Light Output on Battery:

400lm; 3W

Battery Type:

Lithium

Discharge Temperature:

-4°F to 140°F (-20°C to 60°C)

Storage Shelf Life:

2-years

LED Characteristics

Color Temperature:

5000K

Color Accuracy (CRI):

≥80 CRI

R9 Value:

High color performance with R9 less than or equal to 4

Color Consistency:

<5-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.



Technical Specifications (continued)**Installation****Installation Method:**

UL Type B, Ballast Bypass

Base Type:

G13

Construction**Beam Angle:**

140°

Nominal Length:

4 ft

Bulb Shape:

T10

Endcap Material:

Polycarbonate and copper

Enclosure Material:

Polycarbonate and Aluminum

Lens Finish:

Frosted

Compliance**Listings:**

UL Classified, UL Recognized

Environment:

Suitable for use in dry and damp environments

Fixture Rating:

Enclosed

California Energy Commission (CEC) Status:

Lawful for Sales in California

NSF Listed:

NSF/ANSI Standard 2 - Food Equipment (noncontact), Splash Zone, and Non-Food Zone. (Not for Direct Food Zone without additional fixture considerations)

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Certification Model Number:

T10360(T10EM-17-48P-850-SE-BYP)

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

DLC Product Code: S-O04MP6

Other**Accessories:**

T10EM-ACC KIT Test switch kit with lampholders

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Note:

All values are typical (tolerance +/- 10%)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
48	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	48.82	6.3	7
PALLET	1875	48.8	37.8	43.3

Dimension