

**EL Style Malleable Elbows****1 INCH F/F 90 DEGREE MALLEABLE ELBOW****ISO**  
9001:2015  
CERTIFIED

<b>Catalog Number</b>	PREL39
<b>UPC</b>	784011208012

**Description**


PVC coated EL style malleable elbows with female threads only (Female/Female) are used in a conduit run to change direction 90° or to terminate at a fitting or box.

**Application**

- Used in a conduit run to change direction 90 degree or to terminate at a fitting or box

**Features**

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- Various configurations in 10 trade sizes from 1/2" through 4"
- Sealing sleeves on all conduit openings

**General Information**

Trade Size	1
Material	FERROUS METAL
Material	FERROUS METAL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

**Dimensions**

Dimension A (Inches)	2
Nominal Weight (Pounds)	1.2

**Standards**

NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class I, Division 1&2, Groups A,B, C, D
NEC/CEC	Class III

## Technical Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

## Technical Information

Conduit Body	90
Fitting Configuration	F/F
Fitting Type	MALLEABLE ELBOW
Product Category	HAZARDOUS LOCATION FITTING
Product Family	EL Style Malleable Elbows
Rating	Hazardous Location