

Product data sheet

Specifications

SQUARE D



Safety switch, heavy duty, molded case, 225A, 3 pole, 150hp, 600VAC/250VDC, NEMA 7/9

H225XJG

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| | |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device Application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | None |
| Number of Poles | 2 |
| Current Rating | 400 A |
| Voltage Rating | 250 V DC 240 V AC |
| Enclosure Rating | NEMA 7/9 Cast Aluminium |
| Standard Motor Power Rating | 60 hp at 240 V AC 50-60 Hz for 3 phase motors 125 hp at 480 V AC 50-60 Hz for 3 phase motors 150 hp at 600 V AC 50-60 Hz for 3 phase motors |

Complementary

| | |
|-------------------|---------------------------------------------|
| Mounting Type | Surface |
| Wire Size | AWG 1/0...750 kcmil copper or aluminium |
| Tightening torque | 550 lbf.in (62.1 N.m) (AWG 1/0...750 kcmil) |
| Depth | 7.7 in (195.6 mm) |
| Width | 10.93 in (277.62 mm) |
| Height | 22.7 in (576.6 mm) |
| Net Weight | 43.0 lb(US) (19.5 kg) |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10DE100066 |
| Discount Schedule | ODE1 |
| GTIN | 3606481243805 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

| | |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACH Regulation | REACH Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| Halogen content performance | Halogen free plastic parts product |
| PVC free | Yes |

Use Again

Repack and remanufacture

| | |
|---------------------|------------------------------------------|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |