

VHU362DSGL

Safety switch, heavy duty, unfused, viewing window, NEMA 4X, 600V, 60A, 3 pole, ground lugs



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	Field installed kit available
Number of Poles	3
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4X stainless steel 304
Motor power hp	10 Hp at 240 V AC 50/60 Hz for 1 phase motors 20 Hp at 240 V AC 50/60 Hz for 3 phase motors 25 Hp at 480 V AC 50/60 Hz for 1 phase motors 50 Hp at 480 V AC 50/60 Hz for 3 phase motors 30 Hp at 600 V AC 50/60 Hz for 1 phase motors 60 Hp at 600 V AC 50/60 Hz for 3 phase motors 10 Hp at 250 V DC 30 hp at 600 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 50 lbf.in (5.65 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10)
Depth	7.26 in (184.40 mm)
Width	8.92 in (226.57 mm)
Height	16.93 in (430.02 mm)
Net Weight	19.84 lb(US) (9 kg)
Grounding Kit	Factory installation
Service Entrance	Suitable service entrance for USA Suitable service entrance for Mexico

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

Category	US10DE100010
Discount Schedule	0DE1
GTIN	3606485894683
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.37 in (18.732 cm)
Package 1 Width	11.00 in (27.94 cm)
Package 1 Length	18.69 in (47.466 cm)
Package 1 Weight	20.94 lb(US) (9.5 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations