

Conduit Unions UNF & UNY Unions

1-1/2 INCH FEMALE-TO-FEMALE (F/F) ALUMINUM UNF UNION

ISO
9001:2015
CERTIFIED

c
UL
US
LISTED

Catalog Number PRUNF505SA
UPC 784011219308

Description

PVC coated UNF unions are used to connect conduit to conduit or to allow for future changes to the conduit system. Female threads are provided at each end.

Application

- Applicable for Hazardous Locations

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

General Information

Trade Size	1-1/2
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane


Dimensions

Length (Inches)	2.63
Max Diameter (Inches)	3.5

Standards

CSA	C22.2 No.30
NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class III
NEC/CEC	Class I, Division 1 & 2, Groups C, D
UL 1203	E476062

Technical Specification Documents



Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Installer Certification and Tools	AVAILABLE ON WEBSITE
-----------------------------------	----------------------

Chemical Resistance Charts	AVAILABLE ON WEBSITE
----------------------------	----------------------

Performance Specifications	AVAILABLE ON WEBSITE
----------------------------	----------------------

Technical Information

Fitting Configuration	F/F
-----------------------	-----

Fitting Type	UNION
--------------	-------

Product Category	HAZARDOUS LOCATION FITTING
------------------	----------------------------

Product Family	Conduit Unions UNF & UNY Unions
----------------	---------------------------------

Rating	Hazardous Location
--------	--------------------