

# Product data sheet

Specifications

SQUARE D



Contactor, Type L, multipole lighting, electrically held, 30A, 2 pole, 600V, 110/120VAC 50/60Hz coil, NEMA 3R [TAA]

8903LH20V02

**Product availability:** Non-Stock - Not normally stocked in distribution facility

## Main

Product or Component Type	Electrically Held Lighting Contactor
Range of Product	8903L
Control Circuit	Separate control circuit

## Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Inrush power in VA	150 VA 60 Hz 140 VA 50 Hz
Hold-in power consumption in VA	30 VA 60 Hz 30 VA 50 Hz
Current Rating	20 A tungsten 30 A fluorescent
Number of Poles	2P 2 NO
Control Unit	No control units
Pilot Light	No indicator
Electrical Connection	Screw-clamp terminals
Height	16.3 in (414 mm)
Depth	8.6 in (219 mm)
Width	9.8 in (250 mm)

## Environment

Enclosure Type	NEMA 3R painted sheet steel surface
Product Certifications	UL Listed CSA

## Ordering and shipping details

Category	US10CP121321
Discount Schedule	OCP1
GTIN	785901022879
Returnability	No
Country of origin	MX

## Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	10.300 in (26.162 cm)
Package 1 Width	11.00 in (27.94 cm)
Package 1 Length	16.700 in (42.418 cm)
Package weight(Lbs)	18.501 lb(US) (8.392 kg)

## Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

## Use Again

### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No