

# Product data sheet

## Characteristics

# SDSA3650D

Surge protection device, Surgelogic, 40kA, 600 VAC delta, 3 phase, 4 wire, NEMA 4X

### Main



Product	Surge protection device
Range	Surgelogic

### Complementary

Voltage Rating	600 V delta AC
MCOV	1020 V
SCCR	200 kA
Surge Current	40 kA per phase
Nominal Discharge Current	10 kA
Number of Phases	3 phase
Wiring Configuration	3-wire
Local Signalling	Status LED green normal operation
Cable length	24 in (609.60 mm)
Height	3 in (76.20 mm)
Width	3.6 in (91.44 mm)
Depth	3.4 in (86.36 mm)

### Environment

Ambient Operating	149 °F (65 °C)
Enclosure Rating	NEMA 4X
Enclosure Material	Black Plastic
Standards	UL 1449:ed. 4: type I NEC 285: type I CSA C22.2 No 8

### Ordering and shipping details

Category	08462-SURGE PROTECTION SDSA
Discount Schedule	DE1B
GTIN	785901927563
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.20 in (8.128 cm)
Package 1 Width	3.90 in (9.906 cm)
Package 1 Length	5.00 in (12.7 cm)

Package 1 Weight	27.20 oz (771.107 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	6.50 in (16.51 cm)
Package 2 Width	13.70 in (34.798 cm)
Package 2 Length	20.60 in (52.324 cm)
Package 2 Weight	20.96 lb(US) (9.507 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------