

Product data sheet

Characteristics

HU362DSWC

Product availability : Stock - Normally stocked in distribution facility



Price* : 7374.00 USD



Main

Product or component type	Receptacle Switch
Product destination	Plug APJ6485 Crouse-Hinds Arktite
Line Rated Current	60 A
NEMA degree of protection	NEMA 3/3R/4/4X/5/12 stainless steel
Motor power hp	60 hp 600 V AC 50 hp 480 V AC
Disconnecter device type	Non-fusible disconnect switch
Short-circuit current	<= 200 kA
Device mounting	Surface
Number of poles	3
Phase	3 phases
Electrical connection	Receptacle
Product certifications	UL listed
System Voltage	600 V AC
AWG gauge	AWG 12...AWG 2 (aluminium) AWG 14...AWG 2 (copper)
Wiring configuration	4-wire

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	00118 - H&HU SW,W/C-HINDS RECPT-WC
Discount Schedule	DE1
GTIN	00785901077954
Nbr. of units in pkg.	1
Package weight(Lbs)	24
Returnability	N
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------