

Liquidtight Connectors

Features

- Industrial specification grade, screw machined steel, zinc plated
- UL Rated Liquidtight
- Includes sealing washer
- Corrosion resistant protection from moisture & oils
- Designed to protect against excessive vibration

Application

- Bonds Liquidtight conduit to box or enclosure

Standard Material


- Steel

Standard Finish

- Zinc Plated



E148716



Topaz Cat. No.	UPC	Trade Size	Unit Ctn.	Ship Case	Weight Case	A	B	C
470ST	14439	3/8" 1/2" KO	20	200	26	1.09	1.19	.63
471ST	14441	1/2"	20	200	26	1.19	1.34	.63
472ST	14451	3/4"	10	100	18	1.43	1.43	.63
473ST	14461	1"	5	50	16	1.75	1.63	.66
474ST	14471	1 1/4"	5	50	37	2.16	1.84	.67
475ST	14481	1 1/2"	2	20	21	2.38	2.00	.72
476ST	14491	2"	2	20	3	2.88	2.13	.72
477S-USA*	86295	2 1/2"	-	5	260	4.00	3.25	1.50
478S-USA*	85561	3"	-	4	360	4.63	3.88	1.50
479S-USA*	86308	3 1/2"	-	4	445	5.50	4.00	1.50
480S-USA*	85542	4"	-	1	520	5.82	4.00	1.63

*Made in USA