



## PC213-16



### Product Description

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

**Brand:** flexBOX®

**Catalog #:** PC213-16

**Carton Quantity:** 24

**Carton Weight:** 17 lb.

**Width:** 3-1/2 in.

**Depth:** 2-13/16 in.

**Volume:** 21 cu. in.

**Type of Installation:** New Work

**Round Ceiling Box**

**UPC:** 085339983040

**UNSPSC:** 39121316

**Patents:**

U.S. Patent No. 6,365,831 B1

**Country of Origin:** United States of America

### FEATURES

Machine tapped fixture holes

### STANDARDS

ANSI / UL 514C: File No. E30594



### APPLICATION

New work residential construction 2 HR fire  
resistive walls and ceilings (50 lbs. fixture  
support)

### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379  
(Outlet boxes and fittings classified for fire resistance)*

### COLOR

Black

### ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

### MATERIAL

Polycarbonate

### SUPPORT RATING

50 lbs fixture support

### MOUNTING

Adjustable bar hanger - max 16" on center Joist  
application