

Product data sheet

Characteristics

EMT1225CB

Meter socket, ringed, 1 phase, 3 wire, 225A, 5 jaws, 120/240VAC, Series A, test block bypass, EUSERC



Main

Product or Component Type	Meter Socket
Meter socket type	Ringed
Hub type	A ACP closing plate

Complementary

Meter socket rated current	225 A
Number of jaws	5
Bypass type	Test block bypass
Phase	1 phase
[Ue] rated operational voltage	120/240 V AC
Enclosure Material	Steel
Electrical connection	Lugs
Service feed location	OH UG
Wiring configuration	3-wire
Device mounting	Flush
AWG gauge	AWG 6...300 kcmil aluminium/copper)
Height	30.00 in (762.00 mm)
Width	22.44 in (569.98 mm)
Depth	7.50 in (190.50 mm)

Environment

Product Certifications	UL Listed[RETURN]EUSERC
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901335702
Returnability	Yes
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.00 in (22.86 cm)
Package 1 Width	23.00 in (58.42 cm)
Package 1 Length	31.00 in (78.74 cm)
Package 1 Weight	54.50 lb(US) (24.721 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------