

Product data sheet

Characteristics

NF400SFL

Panelboard accessory, NF, lug kit, subfeed, 400A, aluminum



Main

Product	Sub-feed lug
Provided equipment	Screw set 1 Lug 3 Insulated lug 1

Complementary

Current Rating	400 A
Tightening torque	60.18...64.61 lbf.in (6.8...7.3 N.m)

Environment

Product Certifications	cULus
------------------------	-------

Ordering and shipping details

Category	08338-NF (& SHARED) RTI ACCESSORIES
Discount Schedule	PE1A
GTIN	785901538677
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.88 in (12.4 cm)
Package 1 Width	7.91 in (20.1 cm)
Package 1 Length	9.29 in (23.6 cm)
Package 1 Weight	2.78 lb(US) (1.26 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------
