

## Straight Blade Devices

20A, 125V, 2 Pole, 3 Wire Grounding

## Commercial Specification Grade Style Line® Decorator Duplex Receptacles

# HUBBELL

### Features

- Aesthetic Style Line® decorator design
- Smooth face
- Triple wipe contacts



20A 125V  
NEMA 5-20R  
UL CSA  
1 HP



### Ordering Information

Description	Device Color	UPC Number	Catalog Number
Smooth face, Style Line® decorator, back and side wired	Red	783585197593	DR20R

### Listings


UL Listed to UL498 File No. E2186

Certified to CSA, C22.2, No. 42

NEMA® WD-6 Compliant

### Specifications

Face	Nylon
Base	Nylon
Power Contacts	.030 in. (.8) Brass
Ground Contacts	Brass
Wire Clamp	.062 in. (1.6) Nickel plated steel
Terminal Screws	Plated steel
Mounting Strap	.040 in. (1) Galvanized steel
Automatic Self-grounding Staple	Stainless steel
Mounting Screws	Galvanized Steel



### Performance

#### Electrical

Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum

#### Mechanical

Product Identification	Ratings are a permanent part of the device
Terminal Accommodation	#12-#10 AWG copper stranded or solid conductor only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA

#### Environmental

Flammability	UL 94 V-2
Operating Temperatures	Maximum continuous 75°C; minimum -40°C (w/o impact)

### Complementary Products

Wallplate or Weatherproof Cover

StyleLine® Decorator Opening

### Online Resources

Customer Sales Drawings  
eCatalog  
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

