



SKU: GTGC-2-2/0

UPC: 0783669002843

Features & Benefits:

Description: Permaground Copper Ground Clamp, Conductor Range 2/0-2 Sol, 2 Conductors, Rebar Sizes #3-#4, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Ports / Wireways	2
Wire Orientation	Parallel

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	2/0 Sol - 2 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 2 Str
Rebar Size(s) Main	#3 (3/8)

Dimensions

Drive Size Main	7/32
Drive Type Main	Internal Hex
Height (IN)	2.199
Height BX (IN)	6.5
Height (mm)	55.8546
Length (IN)	6
Length (mm)	152.4
Mounting Bolt/Stud Length	2.199
Mounting Bolt/Stud Length (mm)	55.8546
Weight (LB)	0.111
Weight BX (LB)	9.0253
Width (IN)	1.753
Width BX (IN)	12.75
Width (mm)	44.5262

Material and Finish

Clamping Hardware Finish	Tin
Clamping Hardware Material	Stainless steel
Connector Finish	Tin
Insulation	NA
Material	Copper



Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 75
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366900284

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
-------------------	--

Color

Color	Silver
-------	--------

Bolt and Screw Sizes

Clamping Bolt Size	3/8
Wire Binding Screw Size	NA