

REV	DESCRIPTION	BY	DATE	—	----	—	—	—	—
—	—	—	—	—	—	—	—	—	—

TYPICAL BOX WITH INTERIOR

TYPICAL BOX SIDE VIEW

TYPICAL FRONT

TYPICAL SURFACE FRONT
(4 PIECE TRIM – NO DOOR)

BD, BG, BJ, BK, HD, HG, HJ, HR, JD, JG, JJ, JL, JR, QB, QD, QG, QJ and QO when HQO is installed

FRONT BUS CENTER BUS REAR BUS

AØ
BØ
CØ

BRANCH CONNECTION PHASING IS DETERMINED BY CIRCUIT BREAKER SELECTION

TYPICAL SURFACE FRONT
(4 PIECE TRIM – NO DOOR)

REFER TO DP CATALOG CLASS 2110 FOR ADDITIONAL INFORMATION

I-LINE HCJ PANELBOARDS MEET THE APPLICABLE REQUIREMENTS OF UL AND CSA.

BOX: CODE GAUGE STEEL WITH REMOVABLE BLANK ENDWALLS.

FRONT: CODE GAUGE STEEL. GRAY BAKED ENAMEL FINISH ELECTRODEPOSITED OVER CLEANED PHOSPHATIZED STEEL.

LOCK: 73.00/[1854] – 91.00/[2311] HIGH FRONTS HAVE (2) FLUSH LOCKS WITH NSR-251 KEY.

FOR NEMA TYPE 3R APPLICATIONS USE IN CONJUNCTION WITH PBA475.

Main Breaker: LA, LH, LD, LG, LJ, LL

DUAL DIMENSIONS: INCHES MILLIMETERS

MAXIMUM MAIN BREAKER AMPERE RATING	BRANCH BREAKER MOUNTING SPACE (INCHES)	H		A	
		IN	MM	IN	MM
400	27	73.00	1854	47.10	1196
	45				
	81	91.00	2311	65.10	1654

JOB NAME: ---	EQUIPMENT DESIGNATION: ---
JOB LOCATION: ---	EQUIPMENT TYPE: I-LINE HCJ VERTICAL MCB
DRAWN BY: ---	DRAWING TYPE: ---
ENGR: ---	
DATE: FEBRUARY 2019	
DRAWING STATUS: ---	DWG# PBA471HR
	PG 01 OF 01 REV ---