


Ring Terminals – 25 Pack (100 Pack located on Page H7)




- ▶ Vinyl Insulated
- ▶ Electro Tin Plated Copper
- ▶ Expanded Insulation
- ▶ Serrated Barrel
- ▶ 167°F(75°C) 600 Volts Max

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
01012	Red	22-16	#6	.146	.260	.248	.811	.441	.157	.067	.031	25	100
01014	Red	22-16	#8	.169	.315	.276	.866	.441	.157	.067	.031	25	100
01016	Red	22-16	#10	.209	.315	.276	.866	.441	.157	.067	.031	25	100
01018	Red	22-16	1/4	.252	.457	.433	1.102	.441	.157	.067	.031	25	100
01032	Blue	16-14	#6	.146	.260	.248	.823	.453	.177	.091	.031	25	100
01034	Blue	16-14	#8	.169	.335	.307	.917	.453	.177	.091	.031	25	100
01036	Blue	16-14	#10	.209	.335	.307	.917	.453	.177	.091	.031	25	100
01038	Blue	16-14	1/4	.252	.472	.433	1.114	.453	.177	.091	.031	25	100
01040	Blue	16-14	5/16	.331	.472	.433	1.114	.453	.177	.091	.031	25	100
01042	Blue	16-14	3/8	.413	.535	.547	1.260	.453	.177	.091	.031	25	100
01062	Yellow	12-10	#8	.169	.283	.240	.937	.555	.248	.134	.039	25	100
01064	Yellow	12-10	#10	.209	.374	.327	1.067	.555	.248	.134	.039	25	100
01066	Yellow	12-10	1/4	.252	.472	.413	1.205	.555	.248	.134	.039	25	100
01068	Yellow	12-10	5/16	.331	.591	.524	1.382	.555	.248	.134	.039	25	100
01070	Yellow	12-10	3/8	.413	.591	.524	1.382	.555	.248	.134	.039	25	100

Fork/Spade Terminals – 25 Pack (100 Pack located on Page H11)



- ▶ Vinyl Insulated
- ▶ Electro Tin Plated Copper
- ▶ Expanded Insulation
- ▶ Serrated Barrel
- ▶ 167°F(75°C) 600 Volts Max

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
01112	Red	22-16	#6	.146	.252	.256	.874	.441	.157	.067	.030	25	100
01114	Red	22-16	#8	.169	.252	.256	.874	.441	.157	.067	.030	25	100
01116	Red	22-16	#10	.209	.319	.256	.874	.441	.157	.067	.030	25	100
01118	Red	22-16	1/4	.252	.472	.433	1.11	.441	.157	.067	.030	25	100
01132	Blue	16-14	#6	.146	.283	.256	.886	.453	.177	.091	.031	25	100
01134	Blue	16-14	#8	.169	.311	.256	.886	.453	.177	.091	.031	25	100
01136	Blue	16-14	#10	.209	.366	.256	.886	.453	.177	.091	.031	25	100
01138	Blue	16-14	1/4	.252	.472	.433	1.110	.453	.177	.091	.031	25	100
01162	Yellow	12-10	#8	.169	.354	.276	1.047	.555	.248	.134	.039	25	100
01164	Yellow	12-10	#10	.209	.354	.276	1.1047	.555	.248	.134	.039	25	100
01166	Yellow	12-10	1/4	.252	.472	.472	1.283	.555	.248	.134	.039	25	100
01168	Yellow	12-10	5/16	.331	.551	.413	1.244	.555	.248	.134	.039	25	100

Butt Splices - 25 Pack (100 Pack located on Page H24)



- ▶ Vinyl Insulated
- ▶ Electro Tin Plated Copper
- ▶ Expanded Insulation
- ▶ 167°F (75°C) 600 Volts Max

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	L	D	d1	Bag Qty	Master Bag Qty
01182	Red	22-16	.969	.157	.067	25	100
01184	Blue	16-14	.969	.177	.091	25	100
01186	Yellow	12-10	1.043	.248	.134	25	100