

Product data sheet

Specifications



graphic display terminal, Altivar, 240 x 160pixels, IP65

VW3A1111

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Altivar
Range Compatibility	Altivar Process ATV900 Altivar Process ATV600 Altivar Machine ATV340
Accessory / separate part category	Display and signalling accessories
Accessory / Separate Part Type	Display terminal
Accessory / separate part destination	Variable speed drive
Product Specific Application	To control, adjust and configure the drive To save and download configurations To display the current values
IP Degree of Protection	IP65

Complementary

User Language	Spanish Romanian Turkish Polish Swedish Estonian Bulgarian English Russian Greek Danish Hungarian Chinese Norwegian Lituanien French Brazilian German Korean Portuguese Finnish Czech Slovak Taiwanese Dutch Italian Ukrainian
Realtime clock	Built-in
Battery Size	CR2032
Battery life	10 year(s)
Display type	Backlit LCD screen white and red
Messages display capacity	8 lines
Pixel resolution	240 x 160

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Weight	0.4 lb(US) (0.2 kg)
----------------	---------------------

Environment

Ambient Air Temperature for Operation	5...140 °F (-15...60 °C)
---------------------------------------	--------------------------

Ordering and shipping details

Category	US1CP4E22205
Discount Schedule	CP4E
GTIN	3606480702235
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.283 in (5.800 cm)
Package 1 Width	5.512 in (14.000 cm)
Package 1 Length	7.402 in (18.800 cm)
Package weight(Lbs)	10.018 oz (284.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	14.330 lb(US) (6.500 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	80
Package 3 Height	17.717 in (45.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	72.259 lb(US) (32.776 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	104 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	34 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	70 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
SCIP Number	Cd0eb1b0-0b52-4d45-90f6-4bd8d825785f
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	7
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No

Image of product / Alternate images

Alternative





