

# Hospital Grade Surge Suppression Receptacle, Duplex, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Almond

By Hubbell Wiring Device-Kellems  
Catalog # [HBL8362ALSA](#)



Hospital Grade Surge Suppression Receptacle, Duplex, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Almond

## Features

- High-impact nylon face resists breakage
- Automatic grounding clip attached to bridge
- Power-on indicator light verifies instantly that power is available
- Distinctive surge symbol for visual identification of surge suppression receptacle

## Application

Decorator Duplex with Light and Alarm

## Performance

- Electrical - Frequency - 60Hz
- Electrical - Protection Modes - Normal and Common Modes
- Electrical - Response Time - Approximately 5 ns
- Electrical - Transient Suppression - Peak Energy (10 X 100 Qs) Peak Current (8 X 20 Qs)
- Electrical - Voltage - 120V AC + 10% - 15%
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

## General

Catalog Number	HBL8362ALSA
Color	Almond
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED and Audible Alarm
Item Type	Surge Protection Receptacles
Material	Composite
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Response Time	5
Series	Hospital Grade
Specifications	• Base Material - Nylon

• Contact Design - Tandem Modified Bypass	
• Face Material - Nylon	
• Mounting Screws - Steel-Zinc Plated	
• Power Contacts - .031" (.8) Brass	
Type	Duplex
UPC	783585436111

## Dimensions

Display Size	Standard
--------------	----------

## Electrical Ratings

Amperage Rating	20 A
Connectivity	Terminal Screws
Current / Amperage Rating	20 A
Current Rating	20 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

## Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"> <li>• CSA Certified to Specification C22.2 No. 42</li> <li>• Listed to UL Standards 498 Receptacles</li> <li>• UL Listed File E2186</li> </ul>
Nema Rating	5-20R

## Logistics

Carton Quantity	10
-----------------	----

## Product Assets

[Catalogs - WDK Catalog Full 2024](#)  
[Engineering Drawing - HBL8362ALSA AutoCAD Drawing](#)  
[Installation Manuals - WIRING\\_PD1152\\_INSTALLINST](#)

[Literature - SpikeShield® Power Quality Surge Protective Devices](#)  
[Literature - Duct Products Guide](#)

[Sales Drawings - WDK\\_HBL8362\\_DRAWING\\_PDF](#)  
[Specifications - HBL8362ALSA](#)  
[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
WDK-HBL8362ALSA-SPEC-EN | REV 1/2025