



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	1P
Circuit Breaker Type	Standard
Ratings	HACR and Switching Duty rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	65 KA 120/240 V AC 50/60 Hz 65 kA 120 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper or aluminium
Tightening Torque	40.71 lbf.in (4.6 N.m)
Height	2.99 in (76 mm)
Width	0.75 in (19 mm)
Depth	2.91 in (74 mm)
Net Weight	0.33 lb(US) (0.150 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details


Category	00015-QOB CIRCUIT BREAKERS
Discount Schedule	DE2
GTIN	785901255383
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.70 in (1.778 cm)
Package 1 Width	3.40 in (8.636 cm)
Package 1 Length	3.30 in (8.382 cm)
Package 1 Weight	4.38 oz (124.28 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.00 in (10.16 cm)
Package 2 Width	4.20 in (10.668 cm)
Package 2 Length	8.10 in (20.574 cm)

Package 2 Weight	2.85 lb(US) (1.294 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	8.60 in (21.844 cm)
Package 3 Width	8.20 in (20.828 cm)
Package 3 Length	17.10 in (43.434 cm)
Package 3 Weight	29.08 lb(US) (13.189 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------