

Product data sheet

Characteristics

HOM235GFIC

Mini circuit breaker, Homeline, 35A, 2 pole, 120/240VAC, 10kA AIR, ground fault class A, plug in, UL



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	35 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2
Circuit Breaker Type	Ground fault protecting class A 6 mA
Ratings	HACR rated
Electrical Connection	Screw clamp terminals
Wire Size	AWG 12...AWG 4 aluminium)1
Type of Packing	Clam packaging

Complementary

Tightening torque	40.71 lbf.in (4.6 N.m) 0.00...0.02 in ² (2.5...10 mm ²) (AWG 16...AWG 14)
Height	4.23 in (107.44 mm)
Width	2 in (50.80 mm)
Depth	2.98 in (75.69 mm)

Environment

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	00147-HOM 2 POLE GFI CB,40A MAX
Discount Schedule	DE3D
GTIN	785901508250
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.20 in (5.59 cm)
Package 1 Width	4.20 in (10.67 cm)
Package 1 Length	7.00 in (17.78 cm)
Package 1 Weight	1.19 lb(US) (0.54 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information