

PZVR



CEMENT-COATED WALL SLEEVE



A Simple and Effective Solution to Protect Entrances from Water Ingress

Polywater | Hauff-Technik PZVR is a well-designed and effective solution to prevent water ingress through wall entrances. The lightweight UPVC design requires no special equipment to move and can be simply installed in wood or steel formwork. Its proprietary coating creates a homogeneous bond with poured concrete—no puddle flange or engineered ridges needed. This eliminates any space through which water can travel.



FEATURES AND BENEFITS

- **WATERTIGHT**

Bonds to poured concrete with proprietary cement coating

- **CUSTOMIZABLE LENGTH**

When ordered or cut onsite

- **SIMPLE INSTALLATION**

By securing endcap to formwork

- **CLEAN AND DEBRIS-FREE**

Interior is protected with two PE endcaps

- **DURABLE**

Will never rust or corrode



PE covers protect UPVC inside from debris.

CATALOG #	PRODUCTION DESCRIPTION	UNIT
PZVR - 2/xxx	2" (50 mm) diameter wall sleeve	Each
PZVR - 3/xxx	3" (80 mm) diameter wall sleeve	Each
PZVR - 4/xxx	4" (100 mm) diameter wall sleeve	Each
PZVR - 5/xxx	5" (125 mm) diameter wall sleeve	Each
PZVR - 6/xxx	6" (150 mm) diameter wall sleeve	Each
PZVR - 8/xxx	8" (200 mm) diameter wall sleeve	Each
PZVR - 10/xxx	10" (250 mm) diameter wall sleeve	Each
PZVR - 12/xxx	12" (300 mm) diameter wall sleeve	Each

XXX indicates length to be specified to the nearest inch (2.5 cm) increment

Watertightness Testing: Passed testing at 72 psi (5 bar) for 72 hours without water leakage.

Temperature Storage Range: 40°F to 85°F (5°C to 30°C).



Close-up of special cement-bound coating.



Suitable for all wall thicknesses.

Learn more about this product and other sealant solutions from Polywater | Hauff-Technik

polywater-haufftechnik.com | polywater.com

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2021 American Polywater Corporation (08/21) LIT-PZVRFLYER/REV000

Polywater
Solutions at work.

American Polywater Corporation
11222 60th Street N.
Stillwater, MN 55082 USA

+1 651-430-2270
+1 800-328-9384 Toll Free
+1 651-430-3634 Fax
email: support@polywater.com