

YAD4CM12E12, Uninsulated Ring Terminal For 4 AWG, 1-Hole, 1/2" Stud

By Burndy
Catalog # [YAD4CM12E12](#)



Uninsulated Ring Terminal For 4 AWG

Features

- Constructed of pure electrolytic copper for maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Long brazed seam barrel and deep V groove inner serrations provide optimum conductivity reliability and holding power after crimping
- Electro-tin plating to provide durable, long-lasting corrosion resistance
- Wire range is clearly marked on terminal for easy identification
- Inspection hold for an easy visual check of wire insertion
- Long neck terminal permits easy bending and stacking of several terminals on a common stud

Application

The YAD uninsulated OEM lug terminal is constructed of electrolytic copper

Specifications

Buy American Compliant	No
EU RoHS Indicator	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Conductor

Conductor Type	CU C Str-Size;CU C Flex-Size
----------------	------------------------------

Current

Voltage - Maximum	35 kV
-------------------	-------

Dimensions

Package Length	5.75 in
Package Width	3.75 in
Package Weight	2.1 lb.
Dimension - Outside Diameter inch	0.41 in
Dimension - Pad Width inch	0.87 in
Package Height	4.50 in
Dimension - Bolt Size fraction	1/2
Dimension - Hole Size inch	0.51 in
Dimension - Strip Length inch	1/2
Dimension - Stud Size inch	1/2

General

Sub Brand	TERMINALS, HYLUG
Physical Attribute - Tongue Type	Ring
Trade Name	HYLUG™
Feature - Barrel Type	Long
Type	Ring Tongue
UPC 12 Digit	781810549100
UPC 14 Digit GTIN	00781810549100
Material	Copper
UPC	781810549100

Logistics

Minimum Pack Quantity	100
Carton Quantity	1000

Product Assets

[Catalog \[English\]](#)