

Product data sheet

Specifications

SQUARE D



Circuit breaker enclosure,
PowerPacT Q, steel, 70A to 225A,
2 or 3 pole, NEMA 3R

Q23225NRB

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Enclosure
Range of Product	PowerPac Q

Complementary

Current Rating	225 A
Number of Poles	2P 3P
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker PowerPacT
Product Certifications	UL
Circuit Breaker Type	QBL QJL QGL
Voltage Rating	240 V AC
Tightening Torque	28 N.m, AWG 4...300 kcmil
Enclosure Material	Steel
Height	26.3 in (667 mm)
Width	9.9 in (251 mm)
Depth	5.5 in (140 mm)

Ordering and shipping details

Category	US10DE200023
Discount Schedule	0DE2
GTIN	785901470625
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.300 in (16.002 cm)
Package 1 Width	11.000 in (27.940 cm)
Package 1 Length	28.100 in (71.374 cm)
Package weight(Lbs)	22.024 lb(US) (9.990 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Height	42.000 in (106.680 cm)
Package 2 Width	40.000 in (101.600 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	701.00002 lb(US) (317.968 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	76 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	59 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	14 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	7123f656-319e-4ae7-888d-d29a63a4aa90
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Circularity Profile	No need of specific recycling operations
Take-back	No