# 8536SBG2V03

NEMA motor starter, Type S, nonreversing, Size 0, 18A, 5HP at 460VAC, 5kA SCCR, 3 phase, 3 pole, melting alloy, 240VAC coil, NEMA 1



#### Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

Complementary		
NEMA Size	0	
Rated Current	18 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	10.0000000000 in (254.00 mm)	
Width	6.0000000000 in (152.40 mm)	
Depth	5.56 in (141.22 mm)	

### Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed[RETURN]CSA[RETURN]NEMA

#### Ordering and shipping details

US10CP121191	
0CP1	
785901869108	
Yes	
MX	
	0CP1 785901869108 Yes

## Packing Units

cm)
cm)
cm)
(3.36 kg)
2

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
PVC free	Yes

#### Contractual warranty

on the dotter. The training	
Warranty	18 months