

PATRIOT® IN-LINE® 6-Ton Scissor Action, BG/D3 Crimp Jaw, (2) 5.0Ah 18V Li-ion Batteries, 120V-AC Charger, Utility Bag

By Burndy Catalog # PATMD6LW5

PATMD-LW IN-LINE® 6T Scissor Action, BG/D3 Crimp Jaw, 5Ah Li-ion, AC, Utility Bag.



Features

- Interchangeable scissor action crimping and cutting jaws available
- 355° Head rotation
- Uses W and X dies
- · Safety trigger lock and locking jaw tabs
- LED Worklight
- Accepts 2.0Ah-6.0Ah 18V lithium-ion Makita batteries

Application

Crimping and Cutting

General

Application - For Use On Interchangeable Jaws: Crimp:

ACSR, Aluminum, Copper Code/Flex; Cut: ACSR (26/7), Aluminum (AAC), Copper (Soft Drawn), EHS Guy Wire

(sold separately)

Battery Type 5.0Ah 18V Li-lon (Accepts

2.0Ah-6.0Ah Makita LI

Batteries)

Catalog Number PATMD6LW5
Container Type Vinyl Utility Bag

Crimp Force Capacity 6 ton

Die Type W Die and X Die
EU RoHS Indicator Contact Manufacturer
Power Source 120V-AC Charger

Recharge Time 0.75 h

Sub Brand PATRIOT® IN-LINE® CRIMPER

Tool Type Battery Actuated Scissor

Action

Trade Name PATRIOT® IN-LINE®
Type Crimper and Cutter
UPC 621945476882
UPC 12 Digit 621945476882

Dimensions

Dimensions 18.73 in x 2.75 in x 4.38 in

 Height
 4.38 in

 Length
 18.73 in

 Weight
 5.55 lb

 Width
 2.75 in

Electrical Ratings

Operating Voltage 18 VDC

Conductor Related

Crimping Ranges With Appropriate Jaw:

Crimping Capacity: Copper: #10 sol.-500 kcmil, Copper Flex: #8 AWG-350 kcmil, Aluminum: #14 sol.-350 kcmil, ACSR: #14 sol.-4/0 AWG; Cutting Capacity: ACSR (26/7) up to 556.5 kcmil, Aluminum (AAC) up to 636 kcmil, Copper (Soft Drawn) up to 600 kcmil, EHS Guy Wire

up to 3/8"

Logistics

Carton Quantity 1
Minimum Pack Quantity 1

Package Contents Tool, BG/D3 Crimp Jaw, (2)

Batteries, Charger, Utility Bag

Pallet Quantity 30

Product Assets

Catalogs - Full Line BURNDY Catalog Catalogs - Section N - Tooling Customer Notices - Prop 65 Notice

Installation Manuals - BUR_PATMD-LW Sales Drawings - 50054521

SDS - Burndy BAT18VLI SDS Sheet (2022-02)

Video - BURNDY PATMD-LW