

# Product data sheet

Specifications

SQUARE D



Meter mains, QO, CSED, ringless socket, 200A, surface mount, maximum 12 spaces, no bypass

QC12L200C

⚠ To be discontinued on: Dec 31, 2025

⚠ To be discontinued

Product availability: Stock - Normally stocked in distribution facility

## Main

Product or Component Type	Meter Mains
Range of Product	QO

## Complementary

Line Rated Current	200 A
Short-circuit current	22 kA
Network number of phases	1
Meter socket type	Ringless
Mounting	Surface
Number of spaces	12
Number of circuits	0
Number of Tandem Breakers	0
Hub type	A
Electrical connection	Lugs, line side Lugs, service ground
Wire Size	AWG 6...350 kcmil aluminium/copper)line side AWG 12...AWG 2/0 aluminium/copper)service ground
Tightening torque	Main lugs 250 lb.in, AWG 6...350 kcmil, aluminium/copper Lugs 250 lb.in, AWG 4...300 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14...AWG 2/0, copper Service ground 50 lb.in, AWG 12...AWG 2/0, aluminium Branch lugs 35 lb.in, AWG 6...AWG 4, aluminium/copper Branch lugs 25 lb.in, AWG 8, aluminium/copper Branch lugs 20 lb.in, AWG 14...AWG 10, copper Branch lugs 20 lb.in, AWG 12...AWG 10, aluminium Cover 10 lb.in
Disconnect	Service disconnect (ordered separately)
Main Breaker Rating	200 A
Service feed location	OH UG
Bypass type	No bypass
Height	26.16 in (664.46 mm)
Width	14.89 in (378.21 mm)
Depth	6.10 in (154.94 mm)
Bus Rating	200.0 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

---

Product certifications      UL E-6294

## Ordering and shipping details

---

Category	US1DE3A00022
Discount Schedule	DE3A
GTIN	785901001126
Returnability	Yes

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.900 in (14.986 cm)
Package 1 Width	14.800 in (37.592 cm)
Package 1 Length	36.400 in (92.456 cm)
Package weight(Lbs)	40.371 lb(US) (18.312 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	21
Package 2 Height	40.0 in (101.6 cm)
Package 2 Width	40.0 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	848.763 lb(US) (384.992 kg)

## Contractual warranty

---

Warranty      18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

REACH Regulation [REACH Declaration](#)

California proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](#)

## Use Again

### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

Technical Illustration

**Dimensions**

---

Technical Illustration

Wiring diagram

---