



**SKU:** CLNB-400-12-134-4

**UPC:** 0783669680041

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Lug, Conductor Size 400, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Long Barrel, No Sight Window, 45° Bent Tang, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                           |             |
|---------------------------|-------------|
| Barrel Marking            | Hard        |
| Barrel Type               | Long        |
| Connecting Angle          | 45°         |
| Connection                | Compression |
| Contains DE-OX®           | Yes         |
| Flared End                | No          |
| ILSCOs Die Catalog Number | ILD-76      |
| ILSCOs Die Index Number   | I-76        |
| Mounting Hole Type        | Thru        |
| Narrow Tang               | No          |
| Number of Mounting Holes  | 2           |
| Sight Window              | No          |
| Slotted                   | No          |
| Tang End Shape            | Square      |
| Undrilled                 | No          |

### Dimensions

|                              |          |
|------------------------------|----------|
| Barrel Length (IN)           | 2.125    |
| Barrel Length (mm)           | 53.975   |
| Dimension G (IN)             | 0.546    |
| Dimension G (mm)             | 13.8684  |
| Height (IN)                  | 2.774    |
| Height BX (IN)               | 2.0625   |
| Height (mm)                  | 70.4596  |
| Inside Diameter (IN)         | 0.75     |
| Inside Diameter (mm)         | 19.05    |
| Length (IN)                  | 5.193    |
| Length (mm)                  | 131.9022 |
| Mounting Bolt/Stud Size (mm) | 304.8    |
| Mounting Hole Diameter (IN)  | 0.562    |
| Mounting Hole Diameter (mm)  | 14.2748  |
| Mounting Hole Spacing (IN)   | 1.75     |
| Mounting Hole Spacing (mm)   | 44.45    |
| Outside Diameter (IN)        | 0.937    |
| Outside Diameter (mm)        | 23.7998  |
| Strip Length (mm)            | 55.5625  |
| Tang Length (IN)             | 3        |
| Tang Length (mm)             | 76.2     |
| Tang Thickness (IN)          | 0.187    |



|                     |                   |
|---------------------|-------------------|
| Tang Thickness (mm) | 4.7498            |
| Tang Width (IN)     | 1.365             |
| Tang Width (mm)     | 34.671            |
| Weight (LB)         | 0.447347581412388 |
| Weight BX (LB)      | 2.9377            |
| Width (IN)          | 1.365             |
| Width BX (IN)       | 6.875             |
| Width (mm)          | 34.671            |

### Conductor Ranges

|                                                        |                         |
|--------------------------------------------------------|-------------------------|
| Conductor Range AL Stranded (Primary, run, main, line) | NA                      |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                      |
| Conductor Range CU Stranded (Primary, run, main, line) | 400 kcmil               |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                      |
| Expanded Conductor Range                               | 400 kcmil - 4/0 Str     |
| Flex Conductor Range                                   | 300 G,H,I,K,M 313.1 DLO |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Insulation         | NA     |
| Material           | Copper |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### General

|                             |                |
|-----------------------------|----------------|
| Bag Quantity                | 1              |
| Carton Quantity Description | STD PACK QTY 6 |
| Direct Burial               | Yes            |
| Dual Rated                  | No             |
| NEMA Code                   | S-588-3        |
| UPC Code                    | 78366968004    |

### Bolt and Screw Sizes

|                         |     |
|-------------------------|-----|
| Mounting Bolt/Stud Size | 1/2 |
|-------------------------|-----|

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| NEBS Rating              | Level 3                                                                                                             |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |



## Environment and Temperature

Temperature Rating

90°C

## Color

Color

Silver

Color Code

Blue

## Voltage

Voltage Rating

35 kV