



## HANGERMATE VERTICAL MOUNT SCREW FOR CONCRETE, 3/8" ROD, 5/16" SCREW, 2 1/4" SCREW

### CATALOG NUMBER

**HMZG730**



### FEATURES

End-drilled and tapped for attaching threaded components to concrete

Solid, one piece cold formed part; head cannot spin off or unscrew from body

Tapered threads allow for easy starting in pre-drilled hole

### PRODUCT ATTRIBUTES

Material: Steel

Finish: Electrogalvanized

Rod Size: 3/8"

Screw Diameter: 5/16"

Screw Length: 2 1/4"

Drill Bit Diameter: 1/4"

Ultimate Static Load: 2,188 lb

### ADDITIONAL PRODUCT DETAILS

Tested in 3650 psi concrete.

Appropriate safety factors should be applied for design purposes.

## **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### **North America**

+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

### **Europe**

Netherlands: +31 800-0200135  
France: +33 800 901 793

### **Europe**

Germany: 800 1890272  
Other Countries: +31 13 5835404

### **APAC**

Shanghai: + 86 21 2412 1618/19  
Sydney: +61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**