

Reducing Bushings and Couplings

1 TO 3/4 INCH REDUCING BUSHING



|                |              |
|----------------|--------------|
| Catalog Number | PRRE32       |
| UPC            | 784011209200 |

Description

RE style reducers reduce conduit hubs to a smaller size. They are provided with an integral bushing to prevent conductor damage and full, clean cut threads for ease of assembly.



Application

- Reduce conduit hubs to a smaller size

Features

- RE style reducers reduce conduit hubs to a smaller size
- Provided with an integral bushing to prevent conductor damage
- Full, clean cut threads for ease of assembly

General Information

|                 |                                          |
|-----------------|------------------------------------------|
| Trade Size      | 1                                        |
| Material        | FERROUS METAL                            |
| Material        | FERROUS METAL                            |
| Exterior Finish | A nominal .002 inch (2 mil) red urethane |
| Interior Finish | A nominal .002 inch (2 mil) red urethane |

Dimensions

|                         |          |
|-------------------------|----------|
| Nominal Weight (Pounds) | 0.5      |
| Pipe Size (Inches)      | 1 to 3/4 |

Standards

|         |                                      |
|---------|--------------------------------------|
| NEC/CEC | Class II, Division 2, Groups F, G    |
| NEC/CEC | Class II, Division 1, Groups E, F, G |

|         |                                            |
|---------|--------------------------------------------|
| NEC/CEC | Class I, Division 1 & 2, Groups A, B, C, D |
|---------|--------------------------------------------|

|         |           |
|---------|-----------|
| NEC/CEC | Class III |
|---------|-----------|

### Technical Specification Documents

|                                   |                      |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
|-----------------------------------|----------------------|

|                                   |                      |
|-----------------------------------|----------------------|
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
|-----------------------------------|----------------------|

|                                   |                      |
|-----------------------------------|----------------------|
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
|-----------------------------------|----------------------|

|                            |                      |
|----------------------------|----------------------|
| Chemical Resistance Charts | AVAILABLE ON WEBSITE |
|----------------------------|----------------------|

|                            |                      |
|----------------------------|----------------------|
| Performance Specifications | AVAILABLE ON WEBSITE |
|----------------------------|----------------------|

### Technical Information

|                       |          |
|-----------------------|----------|
| Fitting Configuration | REDUCING |
|-----------------------|----------|

|              |         |
|--------------|---------|
| Fitting Type | BUSHING |
|--------------|---------|

|                  |         |
|------------------|---------|
| Product Category | FITTING |
|------------------|---------|

|                |                                 |
|----------------|---------------------------------|
| Product Family | Reducing Bushings and Couplings |
|----------------|---------------------------------|

|                  |          |
|------------------|----------|
| Trade Size Range | 1 to 3/4 |
|------------------|----------|

### Notes

- All REC, RE, and PLGs meet Class I, Division 1 & 2, Groups C, D. REs & PLGs meet the above standards only when used in conjunction with hazardous location fittings.
- Suitable for Groups A & B.