

Straight Liquidtight Connectors

with Insulated Throat - Malleable Iron

Hot Dip Galvanized

Features

- Hot dip galvanized
- Liquidtight, raintight, oiltight
- Tapered threaded male hub NPT
- Insulated throat protects conductors from abrasion damage
- Compact slim diameter with small turning radius

Applications

- To secure, ground and seal liquidtight conduit to a box or enclosure
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

Standard Material


- Malleable iron
- Steel locknut

Standard Finish

- Hot dip galvanized

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div. 2, Class II Div. 1 and 2, Class III Div. 1 and 2 are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
471HDG	03741	1/2"	20	200	33	1.36	1.73
472HDG	03742	3/4"	10	100	24	1.61	1.81
473HDG	03743	1"	5	50	18	1.89	1.85
474HDG	03744	1-1/4"	5	50	30	2.39	2.05
475HDG	03745	1-1/2"	2	20	15	2.62	2.38
476HDG	03746	2"	2	20	23	3.24	2.49
477HDG	03747	2-1/2"	---	1	2	3.89	3.21
478HDG	03748	3"	---	1	3	4.74	3.37
479HDG	03749	3-1/2"	---	1	5	5.31	3.40
480HDG	03751	4"	---	1	5	5.82	3.66