



SKU: CTL-300

UPC: 0783669144680

Features & Benefits:

Description: Surecrimp Copper Compression Sleeve, Conductor Size 300, Long Barrel, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-66
ILSCOs Die Index Number	I-66
Number of Conductors	1
Sight Window	No
Slotted	No

Dimensions

Height (IN)	0.812
Height BX (IN)	2.25
Height (mm)	20.6248
Inside Diameter (IN)	0.66
Inside Diameter (mm)	16.764
Length (IN)	4.125
Length (mm)	104.775
Outside Diameter (IN)	0.812
Outside Diameter (mm)	20.6248
Weight (LB)	0.286
Weight BX (LB)	2.619
Width (IN)	0.812
Width BX (IN)	5
Width (mm)	20.6248

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	300 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	300 kcmil - 2/0 Str
Flex Conductor Range	250 G,H

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366914468

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating	35 kV
----------------	-------