



SKU: PED-8-2/0-Z

UPC: 0783669700060

Features & Benefits:

Description: Aluminum Multi-Tap Connector, Dual Rated, Conductor Range 2/0-14, 8 Ports, UL

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Number of Conductors	8
Number of Poles	1
Number of Ports / Wireways	8

Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	0.73
Height BX (IN)	2.25
Height (mm)	18.542
Length (IN)	7.149
Weight (LB)	0.207
Weight BX (LB)	1.0672
Width (IN)	0.56
Width BX (IN)	4.25
Width (mm)	14.224

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation Material	NA
Wire Binding Hardware Finish	Aluminum
Wire Binding Hardware Material	Tin

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	9/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366970006

Testing Standards

Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

Voltage

Voltage Rating	600 V
----------------	-------