

## KAP350, 350 kcmil pin adaptor, Torque: 100 N lb, Voltage: 600 V.

By Burndy  
Catalog # [KAP350](#)

350 KCMIL AL MECH PIN ADAPTOR



### Features

- AL9CU Dual Rated for both copper and aluminum conductor
- Listed to UL Wire Connector Standard UL486A-486B
- Rated for use with Fine Strand Conductor
- 600 Volt Rated
- Range Taking conductor port
- Plastisol insulated covers provided with each connector

### Application

Terminate "upsized" conductor and/or fine strand conductor into mechanical connectors found in molded case circuit breakers, panel board equipment, and other switchgear.

### Specifications

Buy American Compliant	No
EU RoHS Indicator	Contact Manufacturer

### Conductor

Conductor - Copper DLO Size Range	1/0 AWG - 350 kcmil
Conductor Size	1/0 AWG- 350 KCMIL
Conductor - Copper Str Size Range	1/0 AWG - 350 kcmil
Conductor - Copper Flex H Size Range	1/0 AWG - 350 kcmil
Conductor - Copper Flex I Size Range	1/0 AWG - 350 kcmil
Conductor - Copper Flex K Size Range	1/0 AWG - 350 kcmil
Conductor - AL Str Size Range	1/0 AWG - 350 kcmil

### Configuration

Connector Type	Center Formed Adapter
----------------	-----------------------

### Current

Amperage Rating	350 A
-----------------	-------

### Dimensions

Outside Diameter	1.38 in
Length	2.75 in
Dimension - Strip Length inch	1.11 in
Width	1.5 in
Height	2 in
Dimensions	2.75 in x 1.5 in x 2 in

### Force Related

Installation Torque Recommended in-lb	450
---------------------------------------	-----

### General

Sub Brand Type	Pin Adaptor <ul style="list-style-type: none"> <li>• 1/0 - 350 Mechanical Pin Adaptor</li> <li>• Centered Pin</li> </ul>
Material	Aluminum
Hex Key	3/8 in
UPC	621945493339

### Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	2250

### Product Assets

[Catalog \[English\]](#)