



316 Stainless Steel Drain, M20 - Ex e Class I Div. 2 IP66/4X

By Killark
Catalog # [KDES60M20](#)

316 Stainless Steel Drain, M20 - Ex e Class I Div. 2 IP66/4X.



*Representative Image

Features

- Silicone O-ring supplied as standard and suitable for use in a -55°C to +80°C temperature range.
- 316 stainless steel.
- Internal 316 stainless steel locknut supplied as standard.
- When tightened to the proper torque the joint makes a hose down tight seal for type 4, 4X & IP66 application.

General

Application	
Catalog Number	KDES60M20
EU RoHS Indicator	Contact Manufacturer
Material	316 Stainless Steel
Operating Temperature Celcius Max	80
Operating Temperature Celcius Min	-55 °C
Operating Temperature Range Celcius	-55°C to 80°C
Series	KDE
Type	
UPC	783936121680

Dimensions

Hub Size	M20
Weight	0.25 lb

Certifications And Compliance

ATEX File Number	15ATEX3028X
CSA File Number	2715851
Hazardous Rating(s)	Class I, Divisions 2, Groups A, B, C, D Class I, Zones 1 & 2 Class II, Divisions 1 & 2, Groups E, F, G Class III, Divisions 1 & 2
IECEX File Number	15.0002X
Nema Rating	3, 4, 4X

Logistics

Carton Quantity	10
-----------------	----

Product Assets

- [Catalogs - Killark Catalog](#)
- [Certifications - KDE Series CSA Certification](#)
- [Certifications - KDE Series Drain Breathers IECEx Certification](#)
- [Certifications - KDE Series ATEX Certificate](#)
- [Certifications - KDE Series Declaration of Conformity](#)
- [Customer Notices - Prop 65 Notice](#)
- [Installation Manuals - KDE Series IOM K1458](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
KILL_CA-KDES60M20-SPEC-EN | REV 6/2024