


Product data sheet

Specifications



Wear part, enclosure door, fan for variable speed drive, Altivar Process 600 900, from 55 to 160kW

VX5VPS6001

Product availability: Stock - Normally stocked in distribution facility

Main

Range Compatibility	Altivar Process 600/900
Accessory / Separate Part Type	Fan kit
Accessory / separate part category	Cooling accessory
Product or Component Type	Fan
Product Weight	4.2 lb(US) (1.9 kg)

Complementary

Kit composition	Fan Mounting bracket Instruction sheet
Product compatibility	Variable speed drive ATV630 wall mount 55 kW 200...240 V Variable speed drive ATV630 wall mount 75 kW 200...240 V Variable speed drive ATV630 wall mount 110 kW 380...480 V Variable speed drive ATV630 wall mount 132 kW 380...480 V Variable speed drive ATV630 wall mount 160 kW 380...480 V Variable speed drive ATV930 wall mount 55 kW 200...240 V Variable speed drive ATV930 wall mount 75 kW 200...240 V Variable speed drive ATV930 wall mount 110 kW 380...480 V Variable speed drive ATV930 wall mount 132 kW 380...480 V Variable speed drive ATV930 wall mount 160 kW 380...480 V

Ordering and shipping details

Category	US1CP4E22276
Discount Schedule	CP4E
GTIN	3606480716522
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.858 in (9.800 cm)
Package 1 Width	11.969 in (30.400 cm)
Package 1 Length	11.850 in (30.100 cm)
Package weight(Lbs)	4.438 lb(US) (2.013 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	3

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	15.521 lb(US) (7.040 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No