



SKU: GPL-8

UPC: 0783669262148

Features & Benefits:

Description:Permaground Copper U-Bolt Ground Clamp, Conductor Range 4-8 Sol, Pipe Size 1/2 to 3/4in, Ground Rod Sizes 3/4 to 1in, Rebar Size #8, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	7/8
NPS/IPS Pipe Size	1/2
Rebar Size(s) Main	#8 (1)

Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	3.265
Height BX (IN)	4.875
Height (mm)	82.931
Length (IN)	2.625
Length (mm)	66.675
Weight (LB)	0.799
Weight BX (LB)	2.567
Width (IN)	1.563
Width BX (IN)	3.875
Width (mm)	39.7002

Material and Finish

Conductor Material	Copper
Connector Finish	NA



Insulation

NA

Material

Copper

Wire Binding Hardware Material

Silicon bronze

Additional Technical Specifications

Conductor Type

Solid

Bolt and Screw Sizes

Clamping Bolt Size

1/4

Number of Wire Binding Screws per Port

0

Wire Binding Screw Size

NA

General

Bag Quantity

1

Carton Quantity Description

STD PACK QTY 3

Direct Burial

Yes

Dual Rated

No

NEMA Code

0-000-1

UPC Code

78366926214

Testing Standards

CSA File Number

LR-29601

CSA Standard

C22.2 No. 65-03

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

UL Control Number

667P

UL / CULUS Specification

UL 467 Listed

UL File Number

E34440