

Siemens Low Voltage Circuit Protection General Duty Safety Switch. 3-Pole 3-Fuse and solid neutral Fused in a type 1 enclosure (indoor). Rated 240VAC (200A). Horse power (Std, Time delay) fused: 1-PH 2-W (15, - ), 3-PH 3-W (25, 60), 250VDC (40). Special features: service entrance labeled .



| General technical data                             |   |
|--|---|
| mechanical service life (operating cycles) typical | 8000  |
| fastening method                                   | SURFACE   |
| product function note                              |   |
| number of poles                                    | 3   |
| suitability for operation                          | DISCONNECTING MEAN FOR SERVICE ENTRANCE / LOADS |
| Electricity  |   |
| ampacity   | 200 A   |
| Environmental conditions                           |   |
| ambient temperature during operation maximum       | 85 °C   |
| ambient temperature during operation minimum       | -29 °C  |
| Model  |   |
| product brand name                                 | SIEMENS   |
| product sub brand name                             | VBII  |
| product type designation                           | GENERAL DUTY SWITCH                             |
| type of electrical connection                      | MECHANICAL LUGS                                 |
| Mechanical Design                                  |   |
| design of the housing                              | TYPE 1  |
| design of the actuating element                    | SINGLE THROW                                    |
| material   | STEEL   |
| General product approval                           |   |
| certificate of suitability                         | UL98  |

last modified:

7/18/2024 

