# Product data sheet

Specifications



## Pilot light, Harmony 9001SK, plastic, polycarbonate, fresnel lens, white, 30mm, LED white, 120V

9001SKP38LWW31

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001SK |
| **Product or Component Type** | Pilot light |
| **Device short name** | 9001SK |
| **Lens type** | Fresnel plastic |
| **Light block supply** | Direct 120 V AC/DC |

## Complementary

| | |
|---|---|
| **Bezel material** | Plastic |
| **Mounting diameter** | 1.2 in (30 mm) |
| **Shape of signaling unit head** | Round |
| **Cap/operator or lens colour** | White |
| **Light source** | White LED |
| **Bulb base** | BA 9s |
| **[Us] rated supply voltage** | 120 V AC |
| **Tightening torque** | 7.08 lbf.in (0.8 N.m) IEC 60947-1 |
| **Shape of screw head** | Cross slotted |
| **Connections - terminals** | Screw clamp terminals, 1 x 0.22...2 x 1.5 mm² IEC 60947-1 |
| **[Ith] conventional free air thermal current** | 10 A |
| **Short-circuit protection** | 10 A cartridge fuse IEC 60947-5-1 |
| **[Ui] rated insulation voltage** | 250 V 2)IEC 60947-1 |
| **[Uimp] rated impulse withstand voltage** | 2.5 kV IEC 60947-1 |
| **Operating position** | Any position |
| **CAD overall width** | 2.1 in (54 mm) |
| **CAD overall height** | 2.8 in (70 mm) |
| **CAD overall depth** | 1.7 in (42 mm) |
| **Product Weight** | 0.399 lb(US) (0.181 kg) |
| **Device presentation** | Complete product |
| **Lens type** | Fresnel |
| **[Us] rated supply voltage** | 120 V |
| **Light source colour** | White |
| **Lens material** | Polycarbonate |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Size** | 30 mm |
| **Light source** | LED |

## Environment

| | |
|---|---|
| **Electrical shock protection class** | Class II conforming to IEC 61140 |
| **Protective treatment** | TC |
| **IP Degree of Protection** | IP65/IP66 |
| **NEMA degree of protection** | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X |
| **Vibration resistance** | 7 gn (f= 2…500 Hz) conforming to IEC 60068-2-6 |
| **Shock resistance** | 50 gn IEC 60068-2-27 |
| **Ambient Air Temperature for Operation** | -13…158 °F (-25…70 °C) |
| **Ambient Air Temperature for Storage** | -40…158 °F (-40…70 °C) |
| **Standards** | CSA C22.2 No 14<br>IEC 60947-5-1<br>IEC 60947-1<br>JIS C8201-5-1<br>IEC 60947-5-4<br>UL 508<br>JIS C 852<br>JIS C8201-1 |
| **Product Certifications** | UL 508<br>NEMA |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS121429 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901413219 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 2.300 in (5.842 cm) |
| **Package 1 Width** | 1.900 in (4.826 cm) |
| **Package 1 Length** | 3.700 in (9.398 cm) |
| **Package weight(Lbs)** | 2.880 oz (81.647 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |