



SKU: PTT-2R-0-Z

UPC: 0783669750003

Features & Benefits:

Description: Aluminum Pole Type Overhead Transformer Lug, Dual Rated, Conductor Range 1/0-14, 2 Ports, Right Handed

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	1
Height BX (IN)	2.25
Height (mm)	25.4
Length (IN)	1.875
Length (mm)	47.625
Mounting Bolt/Stud Length (mm)	76.2
Mounting Bolt/Stud Size (mm)	965.2
Weight (LB)	0.399
Weight BX (LB)	1.6984
Width (IN)	0.75
Width BX (IN)	5
Width (mm)	19.05

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes



Mounting Bolt/Stud Size	3/8
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366975000

Testing Standards

ANSI Specification	ANSI C119.6
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL File Number	NA

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol